



PUREGEN CLASSIC SDN. BHD . (989797-V)

NO 10, JALAN PTP 1/2, TAMAN PERINDUSTRIAN TASIK PERDANA,
47120 PUCHONG, SELANGOR DARUL EHSAN, MALAYSIA.

TEL: +603-8066 7100 FAX: +603-8066 9100 EMAIL: puregen@gmail.com

WEBSITE : www.puregen.com.my

River Sand

River Sand is use as filter media in water and waste water treatment. It can be use together with anthracite to perform better result of filtration and filter water quality.

NATURAL PROPERTIES

Appearance	Hard durable cubic sub angular particles
Uncompacted Density	approx. 2.0 t/m ³
Compacted Density	approx. 2.2 t/m ³
Specific Gravity	3.9 – 4.1
Acid Solubility	< 5%
% Retained	> 80% (ASTM Testing Method)

AVAILABLE SIZE RANGE

- a) 0.6 – 1.2mm
- b) 1.2 – 2.4mm
- c) 2.4 – 4.8mm
- d) 6.0 – 12.0mm
- e) 12.0 – 19.0mm
- f) Others size which is not stated in the range above.

TECHNICAL SUPPORT AND KNOW-HOW

PureGen has high technical competent level and technical service departments are staffed by industry leading specialists in the field of all filter media application.

PACKAGING

River Sand is available in 50kg/bag and 1,000kg Jumbo bag.

Kindly contact our technical department for more product information.

All the stated information in this product is reliable, correct and accurate to the best of our product knowledge at the date of its publication. Due to the progressive of Millennium Carbon that improving the performance of our products continuously, we reserve the right to change product specifications without prior notification. No implied warranty or guarantees of product ability, assumes no obligation or liability for the usage of the information in this datasheet. PG RS/0417/REV01